

SAMAC

The way to go

Soil
Asphalt
MACHINES
BY ULDERINK B.V.



Powered by Honda

T115

made in **Holland**

- > For professional use
- > Reliable and durable
- > HONDA engine
- > User friendly

www.samac.nl



Technical specifications

- Force of impact 15 kg
- Compaction depth 35cm
- Vibration frequency 90 Hz
- Width 40 or 45cm
- Operating weight 80kg
- Engine Honda GX160 (air cooled, four-stroke)
- Fuel petrol
- Power output 4kW
- Travel speed up to 24m/min

SINGLE DIRECTION VIBRATORY PLATE

The T15 vibratory plate combines functionality and reliability. **SAMAC** designed this vibratory plate for professional use on smaller sites.

In order to increase operator-comfort, also during transportation, the machine's weight has been kept low. Place and design of the guide handle ensure excellent manoeuvrability, even in confined areas

When we designed the T15 we aimed to realise reliability at a competitive price.

Features:

- The V-belt combined with a centrifugal clutch, guarantees durability of the drive.
- The Honda engine is very reliable and easy to maintain.
- The base plate is wear- and crack resistant by the use of 'High Strength Carbon Sheet'.
- No unnecessary accessories or embellishment.

OPTIONS:

Wheel set

Protective frame/ lifting handle

Synthetic pad for interlocking decorative paving

SAMAC: the way to go.

info@samac.nl

www.samac.nl

W. Röntgenstraat 17
8013 NE Zwolle
t. +31 (0) 38 460 22 00
f. +31 (0) 38 460 22 11
The Netherlands